

Technische specificatie ClimaCalor ventilatorconvector

Kenmerken	ProVC 300	ProVC 400	ProVC 500	ProVC 600
Voedingsspanning (V / Hz)	220V/1-fase/50hz			
Lucht volume				
Hoog (m³/h)	300	400	500	600
Medium (m³/h)	220	300	380	450
Laag (m³/h)	160	230	290	340
Koelcapaciteit (17/22°C)				
Hoog (W)	900	1200	1500	1800
Medium (W)	720	960	1200	1440
Laag (W)	580	780	925	1170
Verwarmingscapaciteit (35/30°C)				
Hoog (W)	1100	1500	1800	2150
Medium (W)	870	1150	1450	1750
Laag (W)	600	750	950	1100
Verwarmingscapaciteit (60/55°C)				
Hoog (W)	2900	3850	4800	5750
Medium (W)	2320	3080	3840	4600
Laag (W)	1510	2000	2500	2990
Geluidsniveau				
Geluidsniveau Hoog (dB(A))	36	39	41	43
Geluidsniveau Medium (dB(A))	34	35	36	37
Geluidsniveau Laag (dB(A))	29	30	31	32
Overige kenmerken				
Water volume (m³/h)	0,31	0,41	0,51	0,61
Drukverlies (kPa)	6	8	10	12
Vermogeninvoer (W)	30	42	49	66
WATERaansluiting (inlaat en uitlaat)	R1/2" inch			
Maximale werkdruk (bar)	16			
Condensatiepijpdikte (mm)	21			
Netto afmetingen (L*B*H) (mm)	1060*145*496			